



**PT. MAJU
LANGGENG
MANDIRI**



Jakarta : (021) 5851478
Semarang : (024) 86402541
Surabaya : (031) 5341056
Bali : (0361) 8495593
Medan : (061) 42065207
Balikpapan : (0542) 877368



www.majulanggeng.co.id



mlm@majulanggeng.co.id



Shotcreting



Grouting



Plastering



Fire Proofing

Semi-dry floor screed

**Self levelling
floor screed**



Plaster/Fine plaster

Shotcrete

Fine grained concrete

Special applications



Putzmeister

Technical Data

Type	M 500 E	M 700 E
Part No	111 598.003	111 599.002
Mixing Vessel	640 l, 500 l Useful capacity	260 l, 200 l, Useful Capacity
Delivery Rate (Theor)	4 m ³ /h	3.8 m ³ /h
Delivery Pressure (max)	7 bar	7 bar
Delivery Range	120 m horizontal, up to 60m vertical (approx.20 storeys)	
Compressor	Required; air output of 4 m ³ /min and 7 bar operating pressure or higher	Required air output of 2,5 m ³ /min and 7 bar operating pressure Higher
Engine	Electric, 18.5 kW, 400 V/50 Hz 3 Phase	Electric 7,5 kW, 400 V/50 Hz 3 Phase
Connection	63 A CEE; max.70m; min. 10 mm ²	32 A CEE;max.70 m min 6 mm
Fuse	50 A	25 A
Weight	1200 kg	700 kg
Lenght x Widht x Height	3730 x 1400 x 1410 mm	2670 x 1280 x 1190 mm
Filling Height	1140 mm	860 mm
Maximum Particle Size	16 mm	16 mm
Chassis	Not Approved For Road Use	Not Approved For Road Use
Pressure Connection	ID65	ID 65
Sound Level LWA/LPA	89 dB/ <85 dB (A)	89 dB/ < 85 dB (A)

M 500 E



M 760 DH



M 700 E



MP 25



Technical Data

Type	M 760 DH	MP 25
Part no	111 646.1XX	111 417.500
Mixing vessel	260 l,200 Useful capacity	115 l
Delivery Rate (theor)*	4 m ³ /h	25 l/min
Delivery Pressure (max)	8 bar	40 bar
Delivery Range***	200 m horizontal/150 m vertical (approx.50 storeys)	Up to 40 m horizontal,15 m vertical
Compressor	5.0 m ³ /min:cut-off pressure 8 bar	0,9 kW,250 l/min
Engine	4 Cylinder Deutz Diesel,46 kW at 2600 rpm (emission stage III A)	5.5 kW at 385 rpm,400 V/50 Hz
Weight (Fully refuelled)	1720 kg	273 kg
Thank capacity	60 l	
Lenght x Width x height	4780X1480X1520 mm	1344x728x1484mm
Filling height	820 mm	984 mm
Maximum particle size	16 mm	4 mm
Chassis	Braked,approved for speeds up to 80 km/h	
Special feature	Basic version	Hose ID 25 for high-quality materials
Sound level LWA/LPA	104 dB / >85 dB (A)	89 dB/ <85 dB (A)
Pump & Water Pump		Worm pump D6-3 & 0,37 kW at 3.6 m ³ /h
Fuse		25 A
Connection		32 A CEE; max. 100 m; min.4 mm ²
Drum Drive		1.1 kW at 24 rpm
Pressure Connection		M35/V 25-40
Maximum particle size		4 mm

Technical Data

Type	P 12	P 13 KA 230
Part No	111 469.060	111 632.xxx(depending on the relevant cust-specific machine config
Mixing Vessel	50 l	170 l
Delivery Rate (Theor)	6-12 l / min	30 - 90 l / min
Delivery Pressure (max)	25 bar	40 bar
Delivery Range	Up to 30 m horizontal, 15 m vertical	Up to 150 m horizontal ,80 m vertical-for site-made plester/fine plaster mix : 60 m horizontal ,40 m vertical
Pump	Worm Pump D5 short	Mechanical piston pump KA 230
Engine	1,4 kW at 94 rpm/1,8 kW at 188 rpm (400 V/50Hz + 60Hz).	-
Fuse	16 A	-
Connection	16 A CEE plug	-
Weight	125 kg	990 kg (unbraked) - 1040 kg (braked)
Lenght x Widht x Height	714 x 696 x 1437 mm	3000x1640x1450mm (unbrake) - 3640x1566x1575mm(braked)
Filling Height	939 mm	1300 mm
Pressure Connection	M 35	M50
Maximum Particle Size	4 mm	-
Sound Level LWA/LPA	89 dB / <85 dB (A)	111 dB / >85 dB (A)
Feed hooper		200 l
Compressor		2-Cylinder 3,5 bar, 300 l/min
Drive		2-Sylinder diesel engine 14,5 kW at 28000 rpm(no emissions le el-non EU
Piston Stroke		130 mm
Piston Diameter		100 mm
Chassis		Unbrake (braked chassis available as an option on all P13 version

P 12



P 718 TD-Non-EU



P 13 KA 230



P 715 TD-Non-EU



Technical Data

Type	P 715 TD Non EU	P 718 TD Non EU
Part no	11 591.400	111 514.400
Feed Hopper	250 l/280 l (with rubber attachment collar)	360 l
Delivery Rate (theor)*	4-17,4 m3/h	4-17,4 m3/h
Delivery Pressure (max)	68 bar	68 bar
Delivery Range***	Up to 300 m horizontal and 100 m vertical,with shotcrete up to 100 m horizontal and 80 m vertical	
Piston pump	2-Cylinder,hydraulic	2-Cylinder, hydraulic
Cylinder diameter	150mm	150 mm
Drive	3nder Deutz diesel engine,34,5 kW(Emission stage III A - non EU	
Drive cylinder diameter	80/45 mm	80/45 mm
Piston stroke	700 mm	700 mm
Strokes/min	27	27
Weight	1850 kg	2320 kg
Lenght x Width x height	4600x1520x1750 mm	4644x1560x1790 mm
Filling height	1180 mm	1180 mm
Maximum particle size	16 mm	32 mm
Machine model	Trailer concrete pump	Trailer concrete pump
Chassis	Road travel chassis,1900 kg	Road travel chassis,2500 kg
Sound level LWA/LPA	108 dB / 85 dB(A)	108 dB / >85 dB (A)



S 5 EVTM

S 5 EV

SP 11 THF



Technical Data

Type no.	S 5 EVTM	SP 11 THF - Stage V
Pan Mixer		
Feed Hopper	100 L	220 l
Pump	Worm Pump 2L6	Worm Pump 2L75
Delivery Rate (theor)*	2,4 m ³ /h 7-40 l / min	0-15 m ³ /h (250 l/min)
Delivery Pressure (max)	25 bar	20 bar
Delivery Range***	Up to 60 L horizontal, 40 m vertical	Up to 80 m horizontal, 40 m vertical
Engine	5.5 kW.400 V/50 Hz	3-cylinder Kubota Diesel, 18.5 kW at 3000 rpm (stage V)
Fuse	16 A	
Connection	32 A CEE; max.100 m;min.	
Mixer Drive	-	
Weight	400 kg	750 kg (max.axle load)
Lenght x Width x height	2290 x 680 x 650 mm	3260 x 1420 x 1160 mm
Filling height		
Maximum particle size	5 mm	8 mm
Pressure connection	M 50	M 50
Special feature	Basic Version	Basic Version
Sound level LWA/LPA	89 dB / < 85 dB (A)	104 dB / <85 dB (A)

Putzmeister



**PT. MAJU
LANGGENG
MANDIRI**

Jakarta : (021) 5851478
 Semarang : (024) 86402541
 Surabaya : (031) 5341056
 Bali : (0361) 8495593
 Medan : (061) 42065207
 Balikpapan : (0542) 877368

www.majulanggeng.co.id
mlm@majulanggeng.co.id

